

MOTORCYCLE

BATTERIES



MOTORCYCLE BATTERIES |

SPECIFICATION

Segment Type	Battery Part No.	External Dimensions in mm		
		L	W	H
PLATINUM ZING	24 RCMC 2.5	79	70	105
	24 RCMC Z4	113	70	85
	24 RCMC Z5	113	70	105
	24 RCMC 5.0	119	59	130
	24 RCMC Z7	113	70	130
	24 RCMC 7.0	148	60	130
	24 RCMC Z8	150	87	105
	24 RCMC 9.0	137	76	134
	24 RCMC 14	132	88	163

FEATURES & ADVANTAGES

- The advance lead calcium - calcium technology with PP case.
- Cast On Strap (COS) group burning of plates.
- The spill-proof VRLA design guards the possibility of Acid leakage.
- The AGM separator give more cranking power and extreme vibration resistance on rough roads.
- Better cranking performance and low self discharge.
- Long lasting performance without D.M. water addition.
- Factory Charged & Ready to use Batteries.

APPLICATIONS

- Two Wheeler





AUTOMOTIVE

BATTERIES



AUTOMOTIVE BATTERIES |

SPECIFICATION

Srgment Type	Container Type		Battery Part No.	External Dimensions in mm			Battery Lauout	Battery Terminal
	IS	JIS		L	W	H		
COPPER VROOM	NS 40	B20	06 RCZK 03PR	197	129	227	1	T1 - Thin type
	NS 40	B20	06 RCZK 05PR	197	129	227	1	T1 - Thin type
	N 25/ NS 40	B20	06 RCAV 027L	197	129	227	0	T1 - Thin type
	N 25/ NS 40	B20	06 RCAV 027R	197	129	227	1	T1 - Thin type
	N 50	D26	06 RCAV 050L	260	173	225	0	T2 - Thick type
	N 50	D26	06 RCAV 050R	260	173	225	1	T2 - Thick type
SILVER VROOM	NS 40	B20	12 RCAV 032L	197	129	227	0	T1 - Thin type
	NS 40	B20	12 RCAV 032R	197	129	227	1	T1 - Thin type
	NS 60(S)	B24	12 RCAV 040L(S)	238	129	227	0	T2 - Thick type
	N 50Z	D26	12 RCAV 060L	260	173	225	0	T2 - Thick type
	N 50Z	D26	12 RCAV 060R	260	173	225	1	T2 - Thick type
	N 70	D31	12 RCAV 070R	306	173	225	1	T2 - Thick type
	N 100	E41	12 RCAV 090L	410	176	234	0	T2 - Thick type
	N 120	F51	12 RCAV 120R	505	182	235	1	T2 - Thick type
	N 150	G51	12 RCAV 150R	508	222	235	1	T2 - Thick type
GOLD VROOM	N 180 / N 200	H52	12 RCAV 180R	521	278	240	1	T2 - Thick type
	NS 40Z	B20	18 RCAV 035L	197	129	227	0	T1 - Thin type
	NS 40Z	B20	18 RCAV 035R	197	129	227	1	T1 - Thin type
	NS 60(S)	B24	18 RCAV 045L(S)	238	129	227	0	T2 - Thick type
	N 50Z	D26	18 RCAV 065L	260	173	225	0	T2 - Thick type
	N 50Z	D26	18 RCAV 065R	260	173	225	1	T2 - Thick type
	N 70Z	D31	18 RCAV 075R	306	173	225	1	T2 - Thick type
	N 100	E41	18 RCAV 100L	410	176	234	0	T2 - Thick type
	N 120 / N 135	F51	18 RCAV 135R	505	182	235	1	T2 - Thick type
	N 150 / N 165	G51	18 RCAV 165R	508	222	235	1	T2 - Thick type
	N 200	H52	18 RCAV 200R	521	278	240	1	T2 - Thick type

FEATURES & ADVANTAGES

- Superior starting, powerful lighting with instant ignition.
- Higher cranking amperes.
- Special paste formulation of battery plates for long life.
- High purity of lead alloy for grids & superfine lead oxide as an active material
- Low self-discharge.
- Extreme vibration resistance especially designed for rough roads.
- Factory charged & Ready to use batteries.

APPLICATIONS

- Three Wheeler
- Car / Jeep
- SUV / MUV
- Tractor / Construction Equipment
- Light Commercial Vehicles
- Heavy Commercial Vehicles
- Truck / Bus





E-RICKSHAW

BATTERIES



E-RICKSHAW BATTERIES |

SPECIFICATION

Segment Type	Container Type		Battery Part No.	External Dimensions in mm			Battery Lauout	Battery Terminal
	IS	JIS		L	W	H		
COPPER eRick	N 100	E41	06 RCER 110FP	410	176	240	0	L Type pole
	N 100	E41	06 RCER 110FP	410	176	240	0	L Type pole

FEATURES & ADVANTAGES

- Very Good Starting power.
- Quick Recharge.
- Extra Mileage.
- Special lead alloy ensures low water loss during high temperature.
- Outstanding sustained performance.
- Special paste additives to enhance re- charging capability of the battery.
- Factory charged & Ready to use batteries.

APPLICATIONS

- E - Rickshaw





TUBULAR

BATTERIES



TUBULAR BATTERIES|

SPECIFICATION

Sagment Type	Container Type		Battery Part No.	External Dimensions in mm			Battery Terminal
	IS	JIS		L	W	H	
SMALL TUBULAR STANDBY BATTERIES							
PLATINUM INVERTO	N 70Z	D3I	24 RCST 050	306	173	235	L Type pole
	N 100	E4I	24 RCST 075	410	176	240	L Type pole
	N 120	F5I	24 RCST 100	505	182	245	L Type pole
	N 150JUMBO	G5I J	24 RCST 125	508	222	245	L Type pole
	N 150 JUMBO	G5I J	24 RCST 150	508	222	245	L Type pole
	N 200 JUMBO	H52 J	24 RCST 175	521	278	280	L Type pole
	N 200 JUMBO	H52 J	24 RCST 200	521	278	280	L Type pole
TALL TUBULAR ST TALL TUBULAR STANDBY BATTERIES							
DIAMOND INVERTO	IT-500	TT	36 RCTT 100	498	187	417	L Type pole
	IT-500	TT	36 RCTT 120	498	187	417	L Type pole
	IT-500	TT	36 RCTT 150	498	187	417	L Type pole
	IT-500	TT	36 RCTT 180	498	187	417	L Type pole
	IT-500	TT	36 RCTT 225	498	187	417	L Type pole
	IT-500	TT	36 RCTT 240	498	187	417	L Type pole

FEATURES & ADVANTAGES

- High Backup with Ultra Low Maintenance.
- Guaranteed Longer Life and High Power output.
- Positive Grid Spines are made with Pressure Die Casting (PDC) machine.
- A unique heavy-duty corrosion-resistant Lead Alloy for positive grids to increase cyclic life in tropical environments.
- Innovative Plate Design offers Low Internal Resistance & High performance.
- Low Antimony Lead Alloy Grids for achieving Low Topping up frequency of Distilled Water.
- Factory Charged & Ready to use Batteries.

APPLICATIONS

- Inverter
- UPS
- Solar
- Railway
- Telecommunication



BRANDS THAT TRUST US

**RADIANT
GROUP**

Kajaria
TRANSFORM YOUR WORLD

BAJAJ
Bajaj Electricals Limited

TATA
TATA POWER

ABB
Power and productivity
for a better world™

NCC
Nagarjuna Construction Company Limited

JOHNSON TILES
NOT JUST TILES. LIFESTYLES.

**P
G
V
C
L**

**D
G
V
C
L**

**M
G
V
C
L**

**U
G
V
C
L**

**G
E
T
C
O**

WATER TREATMENT PLANT
WATER TREATMENT PLANT

WATER TREATMENT PLANT
WATER TREATMENT PLANT

JVVNL

**SOUTHERN
POWER**
DISTRIBUTION COMPANY OF T.G. LTD.

DHBN

WATER TREATMENT PLANT
WATER TREATMENT PLANT

BESCOM
Bangalore Electricity
Supply Company Limited
(Government of Karnataka
Undertaking)

...YOU CAN TOO.